

Vector 75

NEW



**

The new **Vector 75** combines the original Vector 70 LF fluid drag system, with operational enhancements from the class-leading Vector 750. The design retains that familiar Vector feel, without compromising any aspect of camera control.

Incorporated in the Vector 75 is a range of features which address the pressures of today's fast paced and cost conscious production company. This includes smooth operation in both pan and tilt movements with infinite adjustability for both the Perfect Balance and LF drag system. This ensures high levels of control and exceptionally smooth movement in any situation.

The Vector 75 features a centre of gravity range of 8 to 25cm / 3.1 to 9.8" and a maximum payload capacity of 75kg / 165.3lbs ensuring a wide range of camera and accessory combinations can be accommodated.

Like the Vector 750, the Vector 75 employs a unique counterbalance mechanism that does not use springs or cams. Instead a system of mechanical linkages balances cameras with various centre of gravity points, making adjustment simple and eliminating the need for time-consuming cam changes when altering the camera configuration.

- Infinitely adjustable counterbalance and LF drag
- Retractable "T" bar slide plate positioner
- High contrast blue LED level bubble illumination
- Standard prompter bar mountings in the wedge adaptor
- Replaceable pan bar serration disks

Specification
Model No: V4095-0001

	25.5 cm / 10 "
	35.5 cm / 14 "
	35 cm / 13.5 "
	17.9 kg / 39.5 lbs
	75 kg / 165.3 lbs

Tilt Range:

@ 75 kg / 165.3 lbs: ±52°

Platform Adjustment: 33 cm / 13 "

Pan Bar: Single telescopic

Camera Fixing: Wedge adaptor

Levelling Bubble: Illuminated

Base fixing: 4 bolt flat with Quickfix groove

Colour: Black

** Wedge plates not included
Standard wedge part no: 3053-3



An original, **remastered**