



2-Stage Aluminium ENG Pozi-Loc Tripod 100 mm

SKU: 3821-3

Rigid camera support delivering optimum picture control for ENG applications

PRODUCT DESCRIPTION

This two-stage aluminium tripod has an unrivalled height range capability. It is quick and easy to set-up and provides excellent operational flexibility. Vinten tripods are precisely manufactured using the highest quality materials, to optimise torsional rigidity. The Pozi-Loc cam operated clamping system requires low effort with a 90° turn from on to off, providing the user with a positive indication that the tripod is securely locked. The profile of the knob ensures that the camera cables cannot snag

Key features

- Torsional rigidity minimises spring back
- Leg clamps for class leading stiffness
- Toggle leg clamps clearly show the tripod is locked
- Leg catch for easy transport and storage
- Joint clearances minimise free movement when panning

TECHNICAL SPECIFICATIONS

Range	Pozi-Loc
Payload	0 kg to 25 kg 0 lb to 55.11 lb
Material	Aluminium
Weight	3.1 kg 6.83 lb
Spreader Type	Ground Spreader
Bowl size	100 mm
Tripod Stages	2
Interface Compatibility	Ball
Transport Length	71 cm 27.95 in
Height With Spreader	41.6 cm to 156.2 cm 16.38 in to 61.5 in

IN THE BOX

- Pozi-Loc Tripod 2-Stage Aluminium
- User Guide

YOU MAY ALSO LIKE...



[Vision 100 Pan and Tilt Head](#)



[Vision 8AS Pan and Tilt Head](#)



[Vision 10AS Pan and Tilt Head](#)



[flowtech®100 GS](#)