



FPR-210+ with APS

SKU: V3952-0008

Ultimate robotic or manual pedestal with payload up to 95 kg / 210 lbs incorporating APS technology.

PRODUCT DESCRIPTION

Ultimate robotic or manual pedestal with payload up to 95 kg / 210 lbs incorporating APS technology.

Key features:

1. Switchable robotic or manual control for payloads up to 95 kg (210 lbs) - flexible system perfect for multifunctional studios
2. Absolute Positioning System (APS) for unrivalled accuracy of pedestal positioning allowing for track free, zero accumulated error placement
3. Perfect balance and full manual studio pedestal stability and performance
4. Smooth movement and compact 'L' shaped floor targeting that offers precise reference positioning across a wide range of floor surfaces.
5. Adjustable bumper sensitivity
6. Payload capacity can support the combined weight of FH-145 head, camera, lens and prompter/vanity monitor combination up to 66 kg (145 lbs)
7. Customise your workflow with VR option
8. Re assurance of 24 hour global network of service and support.

TECHNICAL SPECIFICATIONS

Range	FPR
Payload	95 kg 209.44 lb
Weight	133.7 kg 294.75 lb
On Shot Stroke	79 mm to 3.11 in to
Manual Mode	Yes
Product Type	Robotic
Height	66 cm to 143 cm 25.98 in to 56.3 in
Floor Speed	25 to 300
Repeatability Percent	±25
Repeatability MM	±0.5
Resolution	<1
Movement Range	Floor and Height
Max Height Speed	150