



HDT-2 Heavy Duty Tripod

SKU: 3902-3

Two-stage Heavy Duty Tripod with dependable strength for studio and OB use

PRODUCT DESCRIPTION

Offering the most extensive height range available from heavy duty tripods the HDT-2 two-stage features increased torsional rigidity and robustness - ideal for large camera and lens combinations in any studio or OB application.

The pinned and glued telescopic leg design provides a wide range of height adjustment whilst offering superior strength and reliability. Set-up has been made even simpler with the addition of engraved leg markings for rapid, even deployment and an integral level bubble allows for fine level adjustment. The new clamping system provides progressive feel to a positive stop which indicates when the leg is locked, ensuring simple and confident clamping.

Key features

- Totally new single piece mid-level spreader for added strength
- Integral carry handle for carrying comfort
- Convenient set-up features - Leg markings for easy height positioning and levelling bubble
- Industry standard combined 4-bolt and Mitchell interface
- Three-position swivel foot - Spike (excellent for wet ground), pad and socket for all applications

TECHNICAL SPECIFICATIONS

Height Without Spreader	51.1 cm to 146 cm 20.12 in to 57.48 in
Range	Heavy Duty
Payload	0 kg to 120 kg 0 lb to 264.55 lb
Material	Aluminium
Weight	15.6 kg 34.39 lb
Bowl size	Four-bolt flat with Quickfix
Tripod Stages	2
Transport Length	73 cm 28.74 in

IN THE BOX

- HDT-2 Tripod
- User Guide

YOU MAY ALSO LIKE...



[Heavy Duty Flexible
Ground Spreader](#)



[Heavy-Duty QUICKFIX
Adaptor](#)



[200 mm Hi-Hat](#)



[HDT OB Dolly](#)