



Osprey Elite S Pedestal (OB)

SKU: V4172-0002

Fully steerable pedestal with perfect balance of its entire extended stroke. Perfect for complete 'on shot' tracking in field applications. Payload up to 80kg / 176lb.



PRODUCT DESCRIPTION

The Osprey Elite S (OB) is a Portable, fully functioning studio pedestal for large payloads up to 80kg / 177lb. It the most versatile pedestal, capable of supporting large Vinten Vector Heads and the latest range of portable or full facility digital cameras and teleprompters. It can track talent eyelines from a seated to standing position 'on shot' with its extended fully balanced range. It has an inlet valve for any air source, making Perfect Balance easy to achieve. There is a storage area for the camera operator. In addition, the Osprey Elite S pedestal includes a pressure gauge for clear and reliable set-up and the detachable skid allows the pedestal to be simply broken down into two sections for easy storage and transportation. It has a selector for both single wheel and all wheel crab steering for working in tight spaces and on shot direction changes. It comes with 16cm / 6.3 inch wheels for greater ground clearance in outside broadcast applications.

Key features

- Full, 2-stage balance range for total 'on shot' elevation, perfect for moving from seated to standing talent in game shows, entertainment shows, drama and performances
- Full crab and steer facilities controlled from a central steering ring for enhanced manoeuvrability and on-shot steering
- Built in pressure gauge for easy counter balance set-up
- Detachable skid for easy transport and storage
- Wheel rim braking mechanism eliminates tyre flat spots for super smooth rolling shots
- Pedestal supplied with Quickfix quick release system & operator storage area
- Column can be adapted to work on dolly track

TECHNICAL SPECIFICATIONS

Range	Osprey
Payload	80 kg 176.37 lb
Weight	50.5 kg 111.33 lb
Application	Drama, Entertainment, Events, Multicam, Turnaround studio, Live on Location, Live Studio
Tracking Width	94 cm 37.01 in
Transit Width	80 cm 31.5 in
Trim Weights	3500
Color	Black
Wheel Locks	Single-point
Pedestal Base	Open
Stages	2
Perfect Balance Stages	2
On Shot Stroke	77 cm to 30.31 in to
Height	58 cm to 145.5 cm 22.83 in to 57.28 in
Narrow Transit Width	70 cm 27.56 in
Wheel Diameter	16 cm 6.3 in
Steering Ring Diameter	53.5 cm 21.06 in

IN THE BOX

- Osprey Elite S (OB) Pedestal
- Quickfix
- Accessory holder
- Manual Pump
- Kick ring
- User Guide

YOU MAY ALSO LIKE...



[Nitrogen Charging Adaptor](#)



[Steering ring, large](#)



[150 mm Levelling Bowl Adaptor](#)



[100 mm Levelling Bowl Adaptor](#)