




Osprey Plus S Pedestal

SKU: V4171-0001

Fully steerable, 2-Stage pedestal with perfectly balanced stage for 'on shot' movement in studios. Payload up to 70kg / 155lb.



PRODUCT DESCRIPTION

The Osprey Plus S is a fully steerable version of the Osprey Plus and is capable of payloads up to 70kg / 155lb. It has 2 stages for achieving very high and low shots, and the upper stage is perfectly balanced for on shot tracking of talent. It has an integral manual pump and an inlet valve for use with an external supply, making Perfect Balance easy to achieve. There is a storage area for the camera operator. In addition, the Osprey Plus pedestal includes a pressure gauge for clear and reliable set-up and the detachable skid allows the pedestal to be simply broken down into two sections for easy storage and transportation. It has a selector for both single wheel and all wheel crab steering for working in tight spaces and on shot direction changes. It comes with 12.5cm / 5 inch wheels and adjustable cable guards for studio use.

Key features

- Upper stage perfect balance for on-shot performance
- Balance assisted second stage for easy elevation and extended height range
- Full crab and steer facilities controlled from a central steering ring for enhanced manoeuvrability and on-shot steering
- Built in pressure gauge and manual pump for easy counter balance set-up
- Detachable skid for easy transport and storage
- Wheel rim braking mechanism eliminates tyre flat spots for super smooth rolling shots
- Pedestal supplied with Quickfix quick release system & operator storage area
- Column can be adapted to work on dolly track

TECHNICAL SPECIFICATIONS

Range	Osprey
Payload	70 kg 154.32 lb
Weight	41.9 kg 92.37 lb
Application	Multicam, Permanent Studio, Live Studio
Tracking Width	97 cm 38.19 in
Transit Width	80 cm 31.5 in
Trim Weights	3500
Color	Black
Wheel Locks	Single-point
Pedestal Base	Open
Stages	2
Perfect Balance Stages	1
On Shot Stroke	41 cm to 16.14 in to
Height	67 cm to 148 cm 26.38 in to 58.27 in
Narrow Transit Width	73 cm 28.74 in
Wheel Diameter	12.5 cm 4.92 in
Steering Ring Diameter	53.5 cm 21.06 in

IN THE BOX

- Osprey Plus S Pedestal
- Quickfix
- Accessory holder
- Manual Pump
- Kick ring
- User Guide

YOU MAY ALSO LIKE...



[Nitrogen Charging Adaptor](#)



[Steering ring, large](#)



[150 mm Levelling Bowl Adaptor](#)



[100 mm Levelling Bowl Adaptor](#)