



Quattro-L Pedestal

SKU: V3852-0003

Four-stage solution with extensive height range for studio applications

PRODUCT DESCRIPTION

Four-stage solution with extensive height range for studio applications.

The Quattro-L is the original pneumatic Perfect Vertical four-stage pedestal for studio applications up to a maximum capacity of 105 kg / 231.5 lbs.

Key features

- Ultra-ridged tri-section 4-stage column for the longest possible vertical stroke and superb stability
- Low volume and low pressure pneumatics for low cost maintenance and safer charging source
- Base jacking facility for easy positioning of cable guards and parking
- Ergonomic, easy access of controls
- Crab and steer control for enhanced manoeuvrability and on-shot steering

TECHNICAL SPECIFICATIONS

Range	Quattro
Payload	105 kg 231.48 lb
Weight	158 kg 348.32 lb
Application	Live Studio
Tracking Width	107 cm 42.13 in
Transit Width	92.4 cm 36.38 in
Trim Weights	7500
Color	Black
Wheel Locks	Single-point
Cable Guards	Single continuous guard, single-point adjustment
Pedestal Base	Skirted
Stages	4
Perfect Balance Stages	4
On Shot Stroke	100 cm to 39.37 in to
Height	45.2 cm to 148 cm 17.8 in to 58.27 in
Wheel Diameter	16 cm 6.3 in
Steering Ring Diameter	74 cm 29.13 in

IN THE BOX

- Quattro-L Pedestal
- User Guide

YOU MAY ALSO LIKE...




[Heavy-Duty QUICKFIX Adaptor](#)



[Nitrogen Charging Adaptor](#)



[Manual Portable Pump](#)



[Mitchell Adaptor to 4-Bolt Flat Base](#)