



System Vision 100 flowtech™100 GS

SKU: VB100-FTGS

System Vision 100 with flowtech®100
carbon fibre tripod, ground spreader and
carry handle



PRODUCT DESCRIPTION

The Vision 100 system with flowtech®100 carbon fibre tripod and ground spreader, is a high-performance professional tripod system designed for camera setups weighing between 7-20 kg / 15.4-44.1 lb.

Combining Perfect Balance with the TF drag system, the Vision 100 allows total control and consistent performance in the toughest conditions. Illuminated drag controls and a digital counterbalance readout ensure simple and repeatable camera set-up in any lighting situation.

Performance tested in extreme conditions, the unique flowtech®100 is easier and faster to deploy and adjust than any other tripod, giving the camera operator ultimate versatility and improving their workflow.

The system is completed with a comfortable carry handle and soft case for protection during transport.

Key Features and Benefits

Vision 100

- Illuminated digital balance readout, drag controls and levelling bubble for quick, precise set-up
- Perfect balance for professional production
- Thin Film drag (TF) for outstanding whip pan in any condition
- Extensive operating temperature from -40°C to +60°C
- Superior performance, year after year

flowtech®100 tripod legs

- Unique quick release brakes - Deploy and adjust your tripod in an instant.
- New ergonomic carbon fibre leg design - Easy to transport and exceptional torsional stiffness
- Versatile hinge lock mechanism - Capture extremely low and high shots
- Extensive endurance and environmental testing - Superior performance and reliability.

flowtech® ground spreader

- Easy foot control to extend spreader arms.
- Removable feet to operate without spreader in low positions.
- Fast and simple setup.

TECHNICAL SPECIFICATIONS

Height Without Spreader	39 cm to 169 cm 15.35 in to 66.54 in
Range	Vision
Counterbalance	Perfect Balance infinitely adjustable spring balance
Payload	7 kg to 20 kg 15.43 lb to 44.09 lb
Material	Carbon Fibre
Weight	7.7 kg 16.98 lb
Drag	TF Drag System with backlit and calibrated control
Bowl size	100 mm
Tripod Stages	2
Application	Documentaries, News, Live Studio
Operating Temperature	-40 °C to 60 °C -40 °F to 140 °F
Interface Compatibility	Ball
Transport Length	83 cm 32.68 in
Head Type	Vision 100
Height	58 cm to 174 cm 22.83 in to 68.5 in

IN THE BOX

- [flowtech®100 GS](#) (V4160-0002)
- [Vision 100 Pan and Tilt Head](#) (3466-3)
- [Soft Case Vision 2-Stage Tripod Systems](#) (3340-3)
- [Carry handle flowtech](#) (S2051-1061)

YOU MAY ALSO LIKE...



System Vision 100
flowtech™100 MS