



System Vision 250 Osprey Plus

SKU: VB250-OP



PRODUCT DESCRIPTION

Combining Perfect Balance with the TF drag system, the Vision 250 allows total control and consistent performance in the toughest conditions. Illuminated drag controls and a digital counterbalance readout ensure simple and repeatable camera set-up in any lighting situation.

This Vision 250 system comes packaged with a Osprey Plus pedestal.

TECHNICAL SPECIFICATIONS

Range	Osprey
Counterbalance	Perfect Balance infinitely adjustable spring balance with readout
Payload	4 kg to 33 kg 8.82 lb to 72.75 lb
Weight	37.3 kg 82.23 lb
Drag	TF Drag System with backlit and calibrated control
Pan Bar Count	2
Bowl size	Flat
Application	Broadcast Studios, Corporate, Events, Houses of Worship
Operating Temperature	-40 °C to 60 °C -40 °F to 140 °F
Camera Compatibility	Can balance System cameras with ENG/EFP lenses with teleprompters, viewfinders & lens controls.
Head Type	Vision 250

IN THE BOX

- [Vision 250F Pan and Tilt Head, Flat Base](#) (3465-3F)
- [Vision Telescopic Pan Bar](#) (3219-91)
- [Osprey Plus Pedestal](#) (V4170-0001)