



System Vision 8AS 2-stage CF PL MS SC

SKU: V8AS-CP2M

The cost effective, professional system

PRODUCT DESCRIPTION

The Vision 8AS incorporates many unique features which have been developed in direct response to customer feedback. Improved access to controls, rapid camera attachment using the Vinten side load system and simple, durable brakes are all designed to cope with the demands of professional operation.

The Vision 8AS is available packaged with a two-stage carbon fibre Pozi-Loc tripod, mid-level spreader and an ergonomically designed carry case.

TECHNICAL SPECIFICATIONS

Range	Vision
Counterbalance	Perfect Balance infinitely adjustable spring balance
Payload	5.5 kg to 14 kg 12.13 lb to 30.86 lb
Material	Carbon Fibre
Weight	7 kg 15.43 lb
Drag	LF Drag System
Bowl size	100 mm
Tripod Stages	2
Application	Commercial/Corporate, Documentaries, News
Operating Temperature	-15 °C to 30 °C 5 °F to 86 °F
Interface Compatibility	Ball
Transport Length	86.6 cm 34.09 in
Head Type	Vision 8AS
Height	57.5 cm to 171.5 cm 22.64 in to 67.52 in

IN THE BOX

- [Vision 8AS Pan and Tilt Head](#) (V4045-0001)
- [2-Stage Carbon Fibre ENG Pozi-Loc Tripod 100 mm](#) (3772-3)
- [Spread-Loc Mid-Level Spreader](#) (3781-3)
- [Soft Case flowtech75 Systems](#) (V4150-1850)

YOU MAY ALSO LIKE...



[System Vision 10AS 2-stage CF PL MS SC](#)



[System Vision 8AS flowtech™100 GS](#)



[System Vision 8AS flowtech™100 MS](#)