



Vision 250 2-Stage Aluminium Tripod System with Mid-level Spreader

SKU: VB250-AP2M

A light, versatile tool for field production
offering a wide payload capacity

PRODUCT DESCRIPTION

The class leading Vision 250 supports the latest portable film and HD cameras complete with viewfinders, prompters and pan bar controls for studio production as well as OB/EFP applications.

The Vision 250 system comes packaged with two-stage aluminium tripod, mid-level spreader, additional telescopic pan bar and soft case.

TECHNICAL SPECIFICATIONS

Range	Vision
Counterbalance	Perfect Balance infinitely adjustable spring balance with readout
Payload	3 kg to 33 kg 6.61 lb to 72.75 lb
Material	Aluminium
Weight	17.3 kg 38.14 lb
Drag	TF Drag System with backlit and calibrated control
Bowl size	150 mm
Tripod Stages	2
Application	Documentaries, News, Sports
Operating Temperature	-40 °C to 60 °C -40 °F to 140 °F
Interface Compatibility	Ball
Transport Length	92 cm 36.22 in
Head Type	Vision 250
Height	68.3 cm to 172.7 cm 26.89 in to 67.99 in

IN THE BOX

- Vision 250 Head (3465-3S)
- Additional Telescopic Pan Bar (3219-91)
- Two-stage Aluminium Pozi-Loc Tripod (V4086-0001)
- Spread-Loc Mid-Level Spreader (3781-3)
- Soft Case (3341-3)