



Vision 8AS 2-Stage Aluminium Tripod System with Ground Spreader

SKU: V8AS-AP2F

The ideal system for professionals using
the latest portable camera configurations

PRODUCT DESCRIPTION

The Vision 8AS incorporates many unique features which have been developed in direct response to customer feedback. Improved access to controls, rapid camera attachment using the Vinten side load system and simple, durable brakes are all designed to cope with the demands of professional operation.

The Vision 8AS is available packaged with an aluminium Pozi-Loc tripod, floor spreader and an ergonomically designed carry case.

TECHNICAL SPECIFICATIONS

Range	Vision
Counterbalance	Perfect Balance infinitely adjustable spring balance
Payload	5.5 kg to 14 kg 12.13 lb to 30.86 lb
Material	Aluminium
Weight	8.5 kg 18.74 lb
Drag	LF Drag System
Bowl size	100 mm
Tripod Stages	2
Application	Commercial/Corporate, Documentaries, News
Operating Temperature	-15 °C to 30 °C 5 °F to 86 °F
Interface Compatibility	Ball
Transport Length	86.6 cm 34.09 in
Head Type	Vision 8AS
Height	77.8 cm to 160.2 cm 30.63 in to 63.07 in

IN THE BOX

- [Vision 8AS Pan and Tilt Head](#) (V4045-0001)
- [2-Stage Aluminium ENG Pozi-Loc Tripod 100 mm](#) (3821-3)
- [Lightweight Ground Spreader](#) (3363-3)
- [Soft Case flowtech75 Systems](#) (V4150-1850)

YOU MAY ALSO LIKE...



[System Vision 8AS](#)
[flowtech™100 GS](#)