

flowtech^m100

The world's fastest deploying tripod now in 100mm.

Vinten presents the award winning flowtech. Providing an incredibly fast, lighweight and easy set up with revolutionary quick release brakes, rubber feet and a carbon fibre mid-level spreader. The award winning flowtech technology is now available in 100mm to support a payload of up to 30kg (66lb).

- Deploy and adjust your tripod in an instant: Unique quick release brakes
- Easy to transport and exceptional torsional stiffness: Ergonomic carbon fibre leg design
- Capture extremely low and high shots: Versatile hinge lock mechanism
- Fast and stable setup in narrow spaces or on uneven terrain: Unique carbon fibre mid-level spreader
- Superior performance and reliability: Extensive endurance and environmental testing



			Tripod techtm 100 MS V4160-0003 Payload range Weight Height Height range in spreaderless mode Height range with mid-level spreader	30kg 2 kg - 7.01lb (tripod only) 26 - 153cm 10.2 - 60.2in 52 - 155cm 20.5 - 61in
	<u>ک</u>		\$	
Height Weight Camera fitting Payload range				
	System Vision 8AS FT MS V8AS-FTMS	System Vision 10AS FT M V10AS-FTMS	VB100-FTMS	
	5.5 - 14.0kg 12.1 - 30.9lb Slide In	6.5 - 17.0kg 14.3 - 37.5lb Slide In	7.0 - 20.0kg 15.4 - 44.1lb Slide In	
	7.2kg / 15.9lb	7.3kg / 16.1lb	7.8kg / 17.lb	
Height range in spreaderless mode	40 - 170cm 15.7 - 66.9in	40 - 170cm 5.7 - 66.9 in	39 - 169cm 15.4 - 66.5in	
Height range with mid-level spreader	69 - 171cm 27.2 - 67.3in	69 - 171cm 27.2 - 67.3in	68 - 170cm 26.8 - 66.9in	

Carbon fibre mid-level spreader For a fast and stable setup in narrow spaces or on uneven terrain. Four locking positions for simple setup and fast repositioning.

Weight: 660g (1.45lb) Built-up radius: 29-41.5cm (11.4-16.3in)

