


# OSPREY elite S

The Osprey Elite S is a portable, fully functioning studio pedestal for large payloads up to 80kg / 176lb. It is the most versatile pedestal, capable of supporting large Vinten Vector Heads and the latest range of portable or full facility digital cameras and teleprompters. It can track talent eyelines from a seated to standing position 'on shot' with its extended fully balanced range. It has an inlet valve for any air source, making Perfect Balance easy to achieve. There is a storage area for the camera operator. In addition, the Osprey Elite S pedestal includes a pressure gauge for clear and reliable set-up and the detachable skid allows the pedestal to be simply broken down into two sections for easy storage and transportation. It has a selector for both single wheel and all wheel crab steering for working in tight spaces and on shot direction changes. It comes with 12.5cm / 5 inch wheels and adjustable cable guards for studio use.

- Full, 2-stage balance range for total 'on shot' elevation, perfect for moving from seated to standing talent in game shows, entertainment shows, drama and performance.
- Full crab and steer facilities controlled from a central steering ring for enhanced manoeuvrability and on-shot steering.
- Built in pressure gauge for easy set-up.
- Detachable skid for easy transport and storage.
- Wheel rim braking mechanism eliminates tyre flat spots for super smooth rolling shots.
- Pedestal supplied with Quickfix quick release system & operator storage area.
- Column can be adapted to work on dolly track with tracking dolly adapters.





**Osprey Elite S**  
V4172-0001

**Osprey Elite S OB**  
V4172-0002

### Technical Specifications

	OSPREY elite >
SKU Studio Version	V4172-0001
SKU OB Version	V4172-0002
Max Payload	80 kg / 176 lb
Height Range Studio Version	66 - 143 cm / 26 - 56 in
Height Range OB Version	68.5 - 145.5 cm / 26.9 - 57.2 in
Number of Stages	2
Number of Perfect Balance Stages	2
On Shot Stroke	77 cm / 30.3 in
Tracking Width	97 cm / 38.2 in
Transit Width	80 cm / 31.5 in
Narrow Transit Width	73 cm / 28.7 in
Steering Ring Diameter	53.3 cm / 21 in
Quickfix Included	YES
Ground Clearance Studio Version	2 cm / 0.8 in
Ground Clearance OB Version	3.45 cm / 1.4 in
Column Drag	YES
Adjustable Cable Guards (Studio Version)	YES
Track Dolly Option Available	YES
Accessory Holder Included	YES
Crab and Steer Modes	YES
Weight	46.5 kg / 102.9 lb

### Accessories



**200mm Hi-Hat**  
3155-3B



**Mitchell head Adaptor**  
3055-3B



**100mm Bowl Adaptor**  
3330-16



**OB Wheels**  
3329-30



**Studio Wheels**  
3329-43



**OB Cable Guards**  
3329-44



**Steering ring, large**  
3429-21



**Tracking Dolly / Skid**  
3369-57



**Tiller Bar**  
3329-21

**OSPREY**  
2 Stage Pedestal Series