

# Quattro-L High Capacity Pedestal

The Vinten Quattro-L High Capacity Pedestal is a high-performance four-stage studio pedestal designed for payloads up to 120kg (264lbs) to support a wide range of studio cameras. With extensive on-shot movement capability and full crab and steer functionality, this pedestal provides the flexibility needed to achieve the perfect shot in any setting.

## Perfect Balance

Camera operators benefit from the perfectly balanced weight distribution, providing noiseless and precise camera elevation with no extra effort. Its pneumatic design guarantees perfect balance throughout its four stages of elevation, allowing effortless camera movement.

## Smooth Moves

The Low-Pressure counterbalance system perfectly compensates for gravity, ensuring smooth camera movement. The four-stage adjustable height design maximises rigidity and minimises torsional twist for the highest level of stability. With an on-shot stroke of 100cm / 39.4", the pedestal provides extremely low angles, giving operators the flexibility to achieve the perfect shot.

## Perfect Position

The ergonomic design ensures easy access to controls, reducing operator fatigue. The detachable Steering Ring provides crab and steer movement and features indicators that allow operators to create quick reference points for camera positions. The pedestal also features retractable wheels for stable parking.

## Global Support

The Quattro-L High Capacity Pedestal is backed by Global Service centres, providing maintenance services such as preventative maintenance, refurbishment, and replacement part installation to ensure continued performance.



## Key Features

- 120kg (264 lbs) payload
- Ultra-ridged trisection 4-stage column for the longest possible vertical stroke and superb stability.
- Low volume and low-pressure pneumatics for low-cost maintenance and safer charging source.
- Fully skirted base
- Base jacking facility from 0 to 28mm ground clearance for easy positioning of cable guards and stable parking.
- Ergonomic, easy access controls
- Crab and steer control for enhanced manoeuvrability and on-shot steering.

## Technical Specifications

|                        |                                                  |
|------------------------|--------------------------------------------------|
| SKU                    | V3852-0004                                       |
| Payload                | 120 kg / 264 lb                                  |
| Stages                 | 4                                                |
| Perfect Balance Stages | 4                                                |
| On shot stroke         | 1m                                               |
| Height                 | 0.46 to 1.49m / 18 to 58.6 in                    |
| Steering               | Crab / Steer                                     |
| Ground Clearance       | 0 - 28mm / 1.1 in                                |
| Tracking Width         | 1.07m / 42.12 in                                 |
| Transit Width          | 925mm / 36.4 in                                  |
| Integrated Pump        | No                                               |
| Cable Guards           | Single continuous guard, single-point adjustment |
| Trim Weights           | 7.5 kg / 16.5 lb                                 |
| Wheel Diameter         | 160mm / 6.2 in                                   |
| Base                   | Skirted                                          |
| Wheel Locks            | Retractable Wheels                               |
| Steering Ring Diameter | 740mm / 29.1 in                                  |
| Weight                 | 158kg / 348.3 lb                                 |

## What's in the box?

- Quattro-L High capacity Pedestal
- User Guide

